Evaluation # | 200303-W (Replaces 970033-W)

Safety & Buildings Division 201 West Washington Avenue P.O. Box 2658 Madison, WI 53701-2658

> INCOMPLETE TEXT AVAILABLE ELECTRONICALLY, CONTACT DEPT.

Wisconsin **Building Products Evaluation**

Material

FR-QuikTM and FR-SystemsTM Rated Roof/Ceiling and Floor/Ceiling Assemblies

Manufacturer

Alpine Engineered Products, Inc. 1950 Marley Drive Haines City, Florida 33844

SCOPE OF EVALUATION

GENERAL: This report evaluates FR-Quik[™] and FR-Systems[™] fire-resistive rated roof/ceiling and floor/ceiling assemblies. Both the FR-QuikTM and FR-SystemsTM registered trademarks, are manufactured by Alpine Engineered Products, Inc. The systems are approved for use in the State of Wisconsin as described in this evaluation.

This review includes the cited International Building Code (IBC) requirements below in accordance with the current Wisconsin Amended IBC Code:

- Fire-Resistance Rating: The FR-QuikTM and FR-SystemsTM both meet the requirements of s. IBC 703.2.
- **Penetrations:** Penetrations through and prescriptive drywall joints on the FR-Quik[™] and FR-Systems[™] shall be in accordance with ss. IBC 706.7, 710.5, 711.4.1 through 711.4.6 and ss. IBC 706.8, 710.6, 712 respectively.

DESCRIPTION AND USE

The FR-QuikTM and FR-SystemsTM are fire-resistance rated assemblies for use in roof/ceiling and floor/ceiling applications. The systems consist of floor or roof sheathing, engineered wood trusses or wood I-beams and gypsum wallboard. The systems incorporate FR-Quik ChannelTM sets that are put in place as the gypsum wallboard is installed in order for the assemblies to perform properly.

FR-SystemsTM General Conditions:

Sheathing: shall be APA-rated sheathing or Sturdi-I-Floor and shall be Exposure 1.

Insulation: per individual test assemblies below, is glass fiber or rock wool with a flame spread rating of 25 or less.